


# MORBARK® 3800XL TRACK WOOD HOG™

## BENEFITS

- An aggressive, productive grinder from the leading manufacturer of industrial grade grinding equipment.
- Process clearing debris, yard waste, storm debris and other mixed woody feedstocks into saleable products.
- Backed by a world-class parts & service support team.
- Long lasting, durable machine that holds its value.
- Proven drive line protection system that protects against catastrophic damage from contaminants.
- Built in a quality-driven factory with highly experienced personnel.



**Morbark Integrated Control Systems**  
Automatically adjusts feed rates, monitor pressures and feed wheel position to maximize production and engine efficiency.



**HAMMERMILL**  
Laser-cut upturn rotor, factory balanced with T-1 hammers offer unsurpassed durability and smooth operation.



**FEED SYSTEM**  
Internal hydraulic drive with no chains and sprockets means lower maintenance, more torque and better durability.



**INFEEB BED**  
WHD 120 infeed chain is heavy duty, rugged and long lasting.

## SPECIFICATIONS

Note: Specifications may vary with equipment options

0622011

### GENERAL

Length (transport).....38' 2"  
Length (operating).....58' 5"  
Height (transport) ..... 12'  
Height (operating) .....16' 4"  
Width .....10' 3"  
Gross weight ..... 77,320 lbs.  
Engine.....CAT, or Cummins  
Horsepower ..... 700 HP to 800 HP  
Fuel capacity (tank) .....280 gallons  
Hydraulic oil capacity.....200 gallons  
Morbark Integrated Control Systems  
320L Caterpillar Undercarriage  
Dust suppression system  
Remote control with tethered back-up system  
Hydraulically operated debris containment door

### INFEEB SYSTEM

59 3/4" x 40" infeed opening  
10 1/4 cubic yard infeed hopper  
Variable speed system  
14' x 59 3/4" live floor with 4-strand WHD 120 chain  
One 34" diameter top compression feed roll with internal drive

### HAMMERMILL AND GRATES

32" diameter x 60 3/8" hammermill  
32" tip swing  
20" diameter rotors with (17) 1 1/4" rotor plates on 7" diameter rotor shaft with 4 7/16" bearings, (8) 2-1/4" hammer retaining rods, (18) 2" thick balanced heavy duty T-1 hammers equipped with (18) 3 1/16" wide double edged replaceable carbide teeth inserts. Three sections of 1" thick wear form steel heavy duty hexagon grates.

Externally adjustable torque limiter

### DISCHARGE SYSTEM

Hydraulically driven aggregate grade belt conveyor, (1) 48" belly belt onto a 36" wide stacking conveyor  
Hydraulic fold for transport.

### OPTIONS

Variety of screen sizes available  
Hydraulic reversing fan  
Hydraulic rod puller  
Air compressor  
Magnetized end pulley  
30 or 36 pattern hammermill  
Externally adjustable break-away torque limiter



800-831-0042 989-866-2381  
www.morbark.com