

Ideal for lot and land clearing contractors and large tree services, this high-capacity, highproduction chipper has more standard features than any other chipper in its class and is offered in a variety of configurations for incredible versatility.

The **Eeger Beever 2230 Brush Chipper** is available is a wide variety of configurations. Select the two-speed, steel track undercarriage with 4.24psi ground pressure and take the chipper to the material. The versatile, high-performance brush chipper, built heavier in critical wear areas, provides optimal performance for in-woods chipping.

## MADE FOR MORE TO KEEP PACE WITH YOU

## **FEATURES AND BENEFITS**

- The powerful TorqMax<sup>™</sup> dual feed wheel compression system generates more than 10,000 ft-lb (4,536 N·m) of material pulling force.
- The Variable Force<sup>™</sup> Hydraulic Down Pressure System eliminates the use of springs and creates up to 1,200 lb (1,627 N·m) of perpetual down pressure.
- The chambered air impeller system increases chip-throwing velocity and aids in discharging light, leafy material.
- 29.125<sup>"</sup> (74 cm) wide x 37.375" (94.9 cm) diameter, six-knife staggered-pocket cutting system with patented removable knife holders increases chipping capacity.
- Bearing-style pivot assembly contours the radius of the drum, increases down pressure efficiency and reduces feed wheel dead space.



226



GENERAL	US	METRIC
Height (adjustable)	10'10"	3.3 m
Width	8'6"	2.6 m
Length	22'7"	6.9 m
Gross weight (approximate)	24,720 lb	11,213 kg
Infeed opening (height x width)	39" x 65"	109.2 x 165.1 cm
Throat opening (height x width)	22" x 30"	55.9 x 76.2 cm
Drum (width x diameter)	29.1" x 37.4"	74 x 94.9 cm
Engine	CAT	
Horsepower	415 HP	309.5 kW
Fuel capacity	65 gallons	246 L
Hydraulic capacity	45 gallons	170.3 L
Frame	2" x 8" Tubular	5.1 x 20.3 cm Tubular
Track	Caterpillar 312B Undercarriage with 500 mm grousers	

## **EQUIPMENT HIGHLIGHTS**

- Dual horizontal feed wheels with TorqMax<sup>™</sup> top feed wheel compression system, hydraulic lift assist, Variable Force<sup>™</sup> constant hydraulic down pressure system with additional manually applied hydraulic down pressure at the valve handle and sprocket driven bottom feed wheel
- Morbark Integrated Control System (MICS) to optimize production and engine efficiency with remote diagnostic capabilities
- 360° height-adjustable, hydraulic swivel discharge chute with chip deflectors
- Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment
- Discharge clean-out door on bottom
- Wireless Remote Control with tethered back-up system

## **OPTIONS INCLUDE**

- Dual Feed Stops on Infeed
- 5-lb (2.27 kg) ABC Fire Extinguisher with Mount

