

LIVE DECKS

OPTIONS MEDIUM DUTY LIVE DECK

- Leg packages.
- 2-arm stop and loader for 2-strand deck, including 10' hoses and fittings.
- 4-arm stop and loader for 3-strand deck, including 10' hoses and fittings.
- Hydraulic control valves to operate deck and stop/loader, less hoses.

OPTIONS HEAVY DUTY LIVE DECK

- Leg packages.
- 2-arm stop and loader for 2-strand deck, including 10' hoses and fittings.
- 4-arm stop and loader for 3-strand deck, including 10' hoses and fittings.
- Hydraulic control valves to operate deck and stop/loader, less hoses.
- Log roll backs stops (idler end, price per strand).
- 1" UHMW duralite wear strip mounted in 5" channel on each strand.



SPECIFICATIONS

Note: Specifications may vary with equipment options

03052010

STANDARD EQUIPMENT

MEDIUM DUTY LIVE DECK

20' long, 2-strand live deck
 10" X 4" X 3/8" steel tube frame strands
 WS-78 chain on strands
 3/4" thick UHMW wear strips for chain to ride on
 Standard strand spacing 6'
 2-7/16" head shaft with ANSON 2500 Series bearings
 Adjustable tail shafts
 Cross sills
 Hydraulic shaft mounted gear reduction drive

HEAVY DUTY LIVE DECK

20' long, 2-strand heavy duty live deck
 12" x 6" x 1/2" steel tube frame strands
 C-131 chain on strands
 16" nose skids
 Standard strand spacing 6'
 2-15/16" head shaft
 Adjustable tail shaft with pillow block bearings
 20' long 3-strand heavy duty live deck with standard strand spacing of 5'6" and 4'6"

and all the above standard equipment
 20' long 4-strand heavy duty live deck with standard strand spacing of 5'4", 4'6", 4' and all of the listed standard equipment
 10 HP electric drive - includes 10 HP electric motor, base, 30 to 1 shaft mounted gear reduction drive, magnetic starter and push button controls
 Hydraulic 30 to 1 shaft mounted gear reduction drive - includes Char-Lynn hydraulic



800-831-0042 989-866-2381
 www.morbark.com