

MATERIAL HANDLING CONVEYOR

STANDARD EQUIPMENT - 14" WIDE

- 20' long x 14" wide paddle type waste conveyor with hydraulic drive.
- Conveyor is fabricated from 10 gauge formed steel panning with enclosed chain return.
- Headshaft and idler shaft are 1-3/4" diameter. C-188 chain with hardwood flited on 24" centers or 81X chain and plastic Driscoppe paddles on 24" centers.

STANDARD EQUIPMENT - 24" Wide

- 20' long x 24" wide paddle type waste conveyor complete with hydraulic drive
- Conveyor is fabricated from 10 gauge formed steel panning with enclosed chain return.
- Headshaft and idler shaft are 2-7/16 diameter. C-188 chain with hardwood flites on 24" centers or 81X chain and plastic Driscoppe paddles on 24" centers



SPECIFICATIONS Note: Specifications may vary with equipment options

03052010

GENERAL 14" Wide

Pan Bed Width	14"
Overall Pan Width	24"
Height	optional
Length	10' - 100'
Weight	1,238 lbs. at 20' long

GENERAL 24" Wide

Pan Bed Width	24"
Overall Pan Width	34"
Height	optional
Length	10' - 100'
Weight	1,394 lbs. at 20' long

DRIVER AND STARTER OPTIONS

5 HP electric drive in lieu of hydraulic drive, includes 5 HP motor, base, and V-belt drive LESS starter (to accommodate up to 30' conveyors)
 10 HP electric drive in lieu of hydraulic drive, includes 10 HP motor, base, and V-belt LESS starter (to accommodate up to 60' conveyors)

OPTIONAL EQUIPMENT

Legs for upright conveyor, 14' wide per set (up to 40' conveyors)
 Legs for upright conveyor, 24" wide per set (up to 40' conveyors)
 Extra set of legs for upright conveyors - 40' - 60' in length
 24" ewide feed hopper
 14" wide feed hopper

RECOMMENDED

OPERATING SETTINGS

Recommended maximum slope is 35 degrees
 Wooden paddles on 15" or 30" centers
 2,000 series Char-Lynn hydraulic drive
 Drag chain conveyor complete with hydraulic drive



800-831-0042 989-866-2381
www.morbark.com